

VI 600-3000 SCL



- Human Interface Device (HID) supported
- Touch Panel (allows to scroll through the parameters)
- Equipped with Boost and Buck AVR to stabilize output voltage

Model dependent



The PowerWalker VI SCL series offers a simple yet effective solution for PCs and other home applications. It is available with Type F (CEE 7/3), Type E (CEE 7/5) and Type G (BS 1363) outlets and features a microprocessor-controlled Automatic Voltage Regulator, which stabilizes voltage within a safe limit by switching to boost and buck modes. The series offers a convenient touch panel which allows you to scroll through most useful parameters.

All UPSs in this series can be turned on directly from battery (cold start function) and the internal batteries can be charged in standby mode. This model comes with a USB port with HID support and can be monitored and controlled using the PowerWalker ViewPower software (available for download from our website) or by directly using the O/S native drivers.

General Features	Values					
Power Capacity	600VA/ 360W	800VA/ 480W	1000VA/ 600W	1500VA/ 900W	2000VA/ 1200W	3000VA/ 1800W
Output Power Factor	0.60					
LINE Mode Full Load	94.0%					
Input Specifications	Values					
Input Voltage Range	162-290 VAC					
Frequency (Synchronized Range)	50Hz or 60Hz					
Input Type	IEC C14 or IEC C14 ^{UK}					IEC C20/ C20 ^{UK}
Output Specifications	Values					
Nominal Output Voltage	230 VAC					
Voltage Regulation	+/- 10%					
Frequency (Battery Mode)	+/- 1Hz					
Outlets	Type F, Type E or Type G (2)			Type F, Type E (4), or Type G (5)		
Battery Specifications	Values					
Batteries	1 x 12V/ 7Ah	1 x 12V/ 9Ah	2 x 12V/ 7Ah	2 x 12V/ 9Ah		
DC Voltage	1 x 12V			2 x 12V		
Recharge Time	4h to 90%			4h-6h to 90%		
Half Load Backup Time	6 min	3 min	5 min	6.5 min	3.7 min	4 min
Transfer Time [AC to Battery]	2-6 ms					