



Intelligent monitoring

Real-time monitoring of product performance.



Short-circuit protection

Auto-cut circuit when short occurs.



Overcharge protection

Prevent battery from overcharging and auto-stop when fully charged.



Overpower protection

Product has dynamic power protection which will auto-stop output when overpower occurs.



Battery balance system

Extend the service life of batteries and ensure the consistency of batteries.



Temperature protection

Guarantee battery working at safe temperature.



Over-current protection

Auto-cut circuit when overcurrent occurs.



Over-voltage protection

Protect product from high or low voltage harm to ensure product and facilities safe.

Portable Power Station



LISTING DETAILS

Modle No: VT-2002

SKU Code: 11445

EAN Code: 3800157692250

MASTER BOX PACKAGING

Qty Per Pallet: 1

Net Weight: 25KG

Product Size: 470*367*292 mm



Drone



Blender



Mini Cooler



Mobile



Laptop



T۱



Fan



Printer




Power Tools



Portable Power Station

DRAWING AND DIMENSION



Provide safe, easy, clean and green energy for you

Our product can be used as an indoor backup power source as well as an outdoor solar generator. High capacity lithium cell and high power output circuit provide sufficient power supplies for illumination, electrical appliances and tools etc.

Inlaid high quality lithium cell

Our product use high quality lithium cell. Which has high capacity density and super long cycle life.

Safe and intelligent

Our product use integration design and intelligent control, With inlaid safe and reliable BMS system and intelligent output control. Our product is safe and stable with reliable circuit designs like real time temperature monitoring, over temperature protection, overcurrent protection and short-circuit protection etc.

High-efficiency Solar Generating Technology

Our product use MPPT (Maximum Power Point Tracking) technology, which can match wider solar charging board, so as to maximize the solar charging efficiency.

Battery Pack : 93.8Ah /44.8V 2016Wh

Ac Rated Output : 2000W

AC Input: 1600W

Solar Charge : DC26V-40V Max 700W solar panel

AC Output: 220V-5.4A 50Hz/2200W- peak Value 4000W

Car Charge Output : 13.5V 9A (max 100W)

USB-A Output: 5v 2.4A

QC Output : 5V/9V/12V/18W

USB-C Output: 5 5V 3A/9V 3A/12V 3A/15V 3A/2OV3.25A PD65W

Wireless Charging Output: 15W

Cycle Life: Cycled > 2000 LiFePO4 Battery











LED High-brightness Display Screen







80% charge in 1 hour



Wide Voltage Input AC 100-240V 50/60Hz input



